



## MAIN FEATURES

Thanks to advanced technological solutions, the Apollo-e and Mini Agri-e electric telehandlers offers performance equal to conventional telehandlers.

Maximum flow rate: 2600 kg  
Lifting height: 5680mm  
Maximum speed 24 km/h  
3 driving modes: Standard, Eco, Power

Optimised transmission to minimise **energy waste**.  
**Tractive force** equal to conventional telehandlers.  
**Low Noise Pump:** vibrations and noise reduced to a minimum.  
**Evolved Adaptive Load Sensing System:** energy savings and longer battery life.  
Electronically controlled **Flow Sharing Distributor** as standard.



**DIECI**

[www.dieci.com](http://www.dieci.com)



### APOLLO-e

SCAN THE QR CODE  
FOR COMPLETE AND  
UPDATED DATA



### MINI AGRI-e

SCAN THE QR CODE  
FOR COMPLETE AND  
UPDATED DATA



**APOLLO-e / MINI AGRI-e**

THE FULL ELECTRIC MINI TELEHANDLER



DOCCT0000133-EN-02

**DIECI**





## APOLLO / MINI AGRI

### THE FIRST FLEXIBLE ELECTRIC TELEHANDLER

Dieci brings an exceptional innovation to the **Full Electric** world: the first **flexible electric telehandler** that adapts to all operational requirements.

An innovative **modular technology** system introduces a whole new concept of an environmentally friendly telehandler, thanks to the application of the unique **E-modular power pack**.

A **customisable, flexible and effective** telehandler for all types of work, which maintains the **high performance** offered by traditional telehandlers while providing **all the advantages of the electric transition**.

## FULL ELECTRIC

### MOTOR

**19 kW** (S2 60)  
Traction motor power

**22 kW** (S3)  
Hydraulic system motor power

### 2 BATTERIES AVAILABLE

~~Standard battery~~ **Standard battery\***

Lithium - **LiFePo4**

**1 OR 2 BATTERIES THAT CAN BE INSERTED AS REQUIRED**

**BATTERY PACK EXPANDABLE AT ANY TIME, EVEN AFTER MARKET, TO OPTIMIZE COSTS AND EFFICIENCY**

A full day's work on a single charge.  
Thermal management, to operate and charge batteries even in the cold.  
Quick and easy battery change.

ECE R100 approved batteries

\*optional

### RECHARGING SYSTEM

**3 charging sockets** as standard, all connected to the onboard battery charger system:



Mode 3 Type 2 (for charging columns)  
220V industrial socket  
380-400V industrial socket

Positioned in **fully accessible** locations on the vehicle, the 3 sockets **recharge when the bonnet is closed**, for greater operator safety and to prevent vandalism. The vehicle is also designed to be connected to various types of external rapid battery chargers.

**EXTERNAL FAST CHARGERS**



The **E-Modular Power Pack** is the innovative and unique modular system developed by Dieci that creates the **first flexible electric telehandler**, capable of adapting perfectly to all operating requirements.

### MODULAR TECHNOLOGY

- Possibility of **choosing the battery pack** based on needs, both at the time of purchase or through After Sales
- **Easy** assembly and disassembly of components from the vehicle

### DUAL BENEFITS

- Doubled energy capacity
- Doubled operating autonomy

**ZERO EMISSIONS**

**LOW MAINTENANCE**

**NO COMPROMISES**

